



**TEGERA® 7363**



[Learn more](#)

**3 STRONG PROTECTIONS IN ONE GLOVE**

Nitrile glove 0,3\* mm/11,8 mil with chemical, cut and heat protection with dipping for non-slip finish. Suitable for work where chemical protection is needed and where there is a risk of cuts and heat damage. Comfortable lining and enhanced dexterity. With Oeko-Tex certificate.

**CHARACTERISTICS**

- High level of protection
- Good fingertip sensitivity
- Durable
- Excellent grip
- Good fit
- Comfortable
- Excellent grip in oily environments

**FUNCTIONS**

- Withstands contact heat up to 100°C
- Waterproof
- Latex-free
- Phthalate-free
- Oil and grease resistant



**PREVENTS RISK OF**

Heat injuries, corrosive injuries, cut injuries, contact with chemicals, contact with moisture, contact with damp, contact with oil, contact with oil and fat

**PRIMARY ENVIRONMENTS OF USE**

Chemical risk environments, corrosive environments, cut risk environments, slippery environments, wet environments, oily and greasy environments, dirty environments, harsh environments

**PRIMARY AREAS OF USE**

Building and construction, chemical technology work, chemical work, construction, glass industry work, hot work, machine operating, metalwork, paper industry work, petro-chemical work, wood industry work

**PRIMARY INDUSTRIES OF USE**

Mining, pulp and paper, chemical, metal fabrication, automotive, service

**TYPE OF WORK**

Medium weight

**CHEMICAL RESISTANCE**

According to EN16523-1:2015. For details, please contact Ejendals.

**SPECIFICATION**

**TYPE** Chemical protection gloves, Cut resistant gloves, Heat protection gloves

**CATEGORY** Cat. III

**THICKNESS** 0,3\* mm (\*chem-layer)

**LINING** Fully lined

**LINING MATERIAL** 18 gg, CRF<sup>®</sup> Technology, Glass fibre thread, HPPE, Nylon, Polyester, Spandex

**LENGTH** 340 mm

**DEXTERITY** 5

**INSIDE** Flock-lined

**GRIP DESIGN** Sandy finish

**COLOUR** Green

**PAIRS PER: BUNDLE/CARTON** 12/60

**DIPPING** Fully dipped

**DIPPING MATERIAL** Nitrile


**CUFF STYLE** Extended safety cuff

**CUT RESISTANCE (EN ISO 13997)** Cut resistance level C

**COMPLIANCE**




TP TC 019:2011



EN 420:2003 +A1:2009



**FEATURES**



**TEST ACCORDING TO EN ISO 374-1:2016**

Tested chemical	A	J	K	M	N	O	P	T
Permeation level	2	5	6	2	3	3	6	6
Degradation %	21,5	5,7	-7,2	5,3	23,8	10,7	-2,0	-7,9

SIZE	ARTICLE NUMBER	EAN
7 S	7363-7	7340118326900
8 M	7363-8	7340118326399
9 L	7363-9	7340118326511
10 XL	7363-10	7340118326634
11 XXL	7363-11	7340118326757

**ejendals**

Limavägen 28, SE-793 32 Leksand, Sweden  
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com