

■ TEGERA® 71000



[Learn more](#)

DOUBLE DIPPED FOR HIGH SAFETY

Double dipped chemical protection PVC glove for allround work with non-slip granulated nitrile finish and seamless lining. 0,2 mm/7,8 mil chemical protection layer. Accelerator-free and phthalate-free, oil and grease resistant. Pre-curved fingers and approved for handling foodstuffs. Soft and flexible design allowing wearers a good all-round working glove.

CHARACTERISTICS

- High level of protection
- Good fingertip sensitivity
- Flexible
- Good grip
- Durable
- Good fit
- Comfortable

FUNCTIONS

- Pre-curved fingers
- Waterproof
- Soft
- Approved for handling foodstuffs
- Protection against chemicals
- Phthalate-free
- Latex-free
- Oil and grease resistant

PREVENTS RISK OF

Corrosive injuries, abrasion injuries, contact with dirt, contact with chemicals, contact with moisture, contact with damp, contact with oil

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Chemical technology work, chemical work, hvac installation, laboratory work, machine operating, metalwork, paint spraying work, paper industry work, petro-chemical work, wood industry work

PRIMARY INDUSTRIES OF USE

Oil, gas, petrochemical, pulp and paper, chemical, metal fabrication, automotive

TYPE OF WORK

Medium weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves

CATEGORY Cat. III

THICKNESS 0,2* mm (*chem-layer)

LINING MATERIAL Nylon, Seamless, Tricot

LENGTH 320 mm

DEXTERITY 5

GRIP DESIGN Granulated

COLOUR Black, Blue

PAIRS PER: BUNDLE/CARTON 6/72

AQL 1.5

DISPLAY TYPE Bulk pack




DIPPING MATERIAL Nitrile, PVC (Vinyl)

INNER MATERIAL SPECIFICATION Nylon

COMPLIANCE




TP TC 019:2011



EN ISO 21420:2020



FEATURES



TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	J	K	L
Permeation level	2	5	2
Degradation %	-16,0	-8,0	-4,9

SIZE		ARTICLE NUMBER	EAN
7	S	71000-7	7340118314242
8	M	71000-8	7340118314259
9	L	71000-9	7340118314266
10	XL	71000-10	7340118314228
11	XXL	71000-11	7340118314235

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
 Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com