



jalas[®] GRIP 3118 LIGHT GRIP

EN ISO 20345:2022 S3S, HRO, FO



[Learn more](#)

Light grip and highest (S3) protection in a low-cut safety shoe built for comfort and stability in style. A split leather and textile upper provides strong yet flexible support for feet and keeps them cool. An oil and heat-resistant nitrile outer sole gives excellent grip, and JALAS[®] aluminium toe cap protection and double impact protection zones in PORON[®] XRD[®] keeps feet safe in environments where highest protection is needed.

CHARACTERISTICS

- Excellent shock absorption
- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable

FUNCTIONS

- Conforms with IEC 61340-5-1 (ESD)
- ProNose toe reinforcement
- Double shock absorption zones
- Anti-static properties
- Ventilating insole
- Heat-resistant outsole
- Oil-resistant outsole
- Water repellent
- Polstered shaft edge



PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, environments with risk for outsole penetration

SPECIFICATION

TYPE Safety footwear, Low shoes

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

COLLECTION Grip

UPPER MATERIAL Split leather, Textile

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide

INSOLE FX2 Pro

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in PORON® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING Laces

SHOELACES LENGTH 100 cm

COLOUR Black, Grey, Yellow

NET WEIGHT, (SIZE 42) 1.25 kg

COMPLIANCE



TP TC 019:2011

EN ISO 20345:2022
S35, HRO, FO



ÖNORM Z 1259



DGUV 112-191

FEATURES



Anti-static properties



Ergothon Shock Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Heat-resistant outsole



Water repellent

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	3118-36	6408487431340
37	4	5	6	3118-37	6408487431357
38	5	5½	6½	3118-38	6408487431364
39	6	6½	7½	3118-39	6408487431371
40	6½	7½	8½	3118-40	6408487431388
41	7	8	9	3118-41	6408487431395
42	8	9	10	3118-42	6408487431401
43	9	9½	11	3118-43	6408487431418
44	10	10½	11½	3118-44	6408487431425
45	10½	11	12½	3118-45	6408487431432
46	11	12	13	3118-46	6408487431449
47	12	13	14	3118-47	6408487431456

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com