



Winter lined neoprene coated glove with chemical-, cut-, and heat protection.

TEGERA® 494



[Learn more](#)

HIGH SAFETY MULTI PROTECTION GLOVE

Winter lined neoprene coated glove with chemical-, cut-, and heat protection. 0,5 mm/19,6 mil. Crinkled grip pattern for extra grip. Withstands contact heat up to 500°C/932°F. High level of protection. Latex-free and extra-long.

CHARACTERISTICS

- High level of protection
- Good grip
- Warm

FUNCTIONS

- Protection against chemicals
- Waterproof
- Extra long
- Phthalate-free
- Latex-free
- Withstands contact heat up to 500°C

PREVENTS RISK OF

Burn injuries, heat injuries, corrosive injuries, cut injuries, contact with chemicals, contact with moisture, contact with damp, contact with oil, contact with cold

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, cold environments, warm environments, moist environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Chemical technology work, chemical work, metalwork, mining, paper industry work, petro-chemical work

PRIMARY INDUSTRIES OF USE

Agriculture, oil, gas, petrochemical, pulp and paper, chemical, rubber and plastic, metal fabrication

TYPE OF WORK

Heavy weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves, Cold insulation gloves, Cut resistant gloves, Heat protection gloves

CATEGORY Cat. III

THICKNESS 0,5* mm (*chem-layer)

LINING Winter-lined

LENGTH 450 mm

GRIP DESIGN Crinkled grip pattern

COLOUR Black

PAIRS PER: BUNDLE/CARTON 6/36

AQL 0.65

DIPPING MATERIAL Neoprene

CUT RESISTANCE (EN ISO 13997) Cut resistance level C




INNER MATERIAL SPECIFICATION Cotton

OUTER MATERIAL SPECIFICATION Chloroprene


COMPLIANCE



TP TC 019:2011




EN ISO 21420:2020



EN 511 cl. 5.2 Flexibility behavior (-20°C)

FEATURES



TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	K	L	P	T
Permeation level	6	2	6	6
Degradation %	8,8	15,5	8,8	1,0

SIZE		ARTICLE NUMBER	EAN
10	XL	494-10	7392626035577

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com