



A tough, mid-cut safety boot with highest protection level (S3) and BOA® Fit System built for heavy work.

**jalas® HEAVY DUTY 1278**

EN ISO 20345:2011 S3, SRC, CI, HRO, HI ASTM F2413-18 M/I/C SD 35 PR



[Learn more](#)

A tough, mid-cut safety boot with highest protection level (S3) and BOA® Fit System built for heavy work. The PU-coated leather and microfibre upper gives excellent foot protection and additional ankle support. The oil and heat-resistant nitrile outer sole gives excellent grip, and JALAS® Composite Toe Cap, nail protection in steel and double impact protection zones in PORON® XRD® mean safer workdays.

**CHARACTERISTICS**

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

**FUNCTIONS**

- ProNose toe reinforcement
- Pull loops
- Water repellent
- Heat-resistant outsole
- Oil-resistant outsole
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- BOA® Fit System
- Bellows tongue
- TPU heel support
- Padded shaft edge in memory foam
- Ankle support
- Ergonomically shaped



**PREVENTS RISK OF**

Toe injuries, nail penetration, sprain injuries, antistatic

**PRIMARY ENVIRONMENTS OF USE**

Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration, oily and greasy environments, dirty environments, harsh environments

**SPECIFICATION**

**TYPE** Safety footwear, Boots/Ankle boots

**CATEGORY** Cat. II

**NAIL PROTECTION MATERIAL** Steel

**FITTING** Regular

**COLLECTION** Heavy Duty

**UPPER MATERIAL** PU-coated leather

**PRONOSE MATERIAL** PU

**TOECAP MATERIAL** Composite

**LINING MATERIAL** Polyester, polyamide

**INSOLE** FX2 Climate

**INNERSOLE MATERIAL** Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in Poron® XRD®

**MIDSOLE MATERIAL** PU midsole

**OUTSOLE MATERIAL** Nitrile rubber outsole

**FASTENING** BOA® Fit System

**COLOUR** Black, Blue

**NET WEIGHT, (SIZE 42)** 1.4 kg

**COMPLIANCE**



TP TC 019:2011

EN ISO 20345:2011  
S3, SRC, CI, HRO, HI

ASTM F2413-18  
M/I/C  
SD 35 PR



ÖNORM Z 1259



DGVU 112-191

**FEATURES**



Anti-static properties



Oil-resistant outsole



ProNose toe reinforcement



Composite toecap



Ergothan Shock Absorption System



ESD



Nail protection in steel



Heat-resistant outsole



Water repellent

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3½	4	1278-35	6408487506086
36	3	4	5	1278-36	6408487506093
37	4	5	6	1278-37	6408487506109
38	5	5½	6½	1278-38	6408487506116
39	6	6½	7½	1278-39	6408487506123
40	6½	7½	8½	1278-40	6408487506130
41	7	8	9	1278-41	6408487506147
42	8	9	10	1278-42	6408487506154
43	9	9½	11	1278-43	6408487506161
44	10	10½	11½	1278-44	6408487506178
45	10½	11	12½	1278-45	6408487506185
46	11	12	13	1278-46	6408487506192
47	12	13	14	1278-47	6408487506208
48	13	13½	14½	1278-48	6408487506215

**ejendals**

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com