



TEGERA® 12910



[Learn more](#)

PERFECT TO USE WHEN CLEANING TANKS

A super-long, high-safety glove 0,3 mm/11,8 mil with sandy finish for a secure grip. The glove protects against chemicals and is perfect to use when cleaning tanks. It is oil resistant thanks to triple PVC coating and stays soft in cold conditions. Phthalate-free.

CHARACTERISTICS

- High level of protection
- Good fit
- Durable
- Good grip
- Comfortable

FUNCTIONS

- Waterproof
- Extra long
- Protection against chemicals
- Phthalate-free
- Oil and grease resistant
- Soft

PREVENTS RISK OF

Corrosive injuries, puncturing, abrasion injuries, contact with dirt, contact with chemicals, contact with moisture, contact with damp, contact with oil

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Hvac installation, petro-chemical work, chemical work, chemical technology work, paper industry work, decontamination, sanitation, cleaning, laboratory work, fishing industry work, marine work

PRIMARY INDUSTRIES OF USE

Agriculture, oil, gas, petrochemical, pulp and paper, chemical

TYPE OF WORK

Heavy weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves

CATEGORY Cat. III

THICKNESS 0,3* mm (*chem-layer)

LINING MATERIAL Seamless, Cotton

LENGTH 700 mm

DEXTERITY 5

GRIP DESIGN Sandy finish

COLOUR Blue

PAIRS PER: BUNDLE/CARTON 6/36

AQL 0.65

DIPPING MATERIAL PVC (Vinyl)

INNER MATERIAL SPECIFICATION Cotton


OUTER MATERIAL SPECIFICATION Polyvinyl chloride

COMPLIANCE


CE 0598

TP TC 019:2011


UK 0321


 Information/UIS

EAC

 EN ISO 374-1:2016/A1:2018 Type B JKL

 EN 374-3:2003


 EN ISO 374-5:2016

 EN 388:2016+A1:2018 4121X

EN ISO 21420:2020

FEATURES

 Waterproof

 Chemical protection

TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	J	K	L
Permeation level	2	6	3
Degradation %	9,5	-5,9	0,2

SIZE	ARTICLE NUMBER	EAN
7 S	12910-7	7392626074385
8 M	12910-8	7392626074392
9 L	12910-9	7392626074408
10 XL	12910-10	7392626074361
11 XXL	12910-11	7392626074378

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com