



TEGERA® 12930



[Learn more](#)

SOFT PVC GLOVE, REGULAR SLEEVE

Double-dipped PVC chemical protection glove with a regular sleeve. It withstands contact heat up to 100°C/212°F, offers a good grip in oil, features a knitted lining, is phthalate-free, and has a 0.2 mm/7,8 mil chemical protection layer. Pre-curved fingers, a comfortable and soft design, lead to less hand fatigue and improved work efficiency

CHARACTERISTICS

- High level of protection
- Durable
- Excellent grip
- Flexible
- Good fit
- Comfortable
- Good grip in oily environments

FUNCTIONS

- Withstands contact heat up to 100°C
- Pre-curved fingers
- Waterproof
- Protection against chemicals
- Latex-free
- Phthalate-free
- Oil and grease resistant

PREVENTS RISK OF

Heat injuries, corrosive injuries, contact with dirt, contact with chemicals, contact with moisture, contact with damp, contact with oil

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Building and construction, hvac installation, construction, soil preparation, concrete work, mining, agricultural work, forest work, marine work, fishing industry work, fishing, petro-chemical work, chemical work, chemical technology work, laboratory work, paper industry work, decontamination, sanitation

PRIMARY INDUSTRIES OF USE

Agriculture, mining, oil, gas, petrochemical, pulp and paper, chemical, rubber and plastic, automotive

TYPE OF WORK

Heavy weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves, Heat protection gloves

CATEGORY Cat. III

THICKNESS 0,2* mm (*chem-layer)

LINING MATERIAL Nylon, Seamless

LENGTH 300 mm

GRIP DESIGN Granulated

COLOUR Blue, Black

PAIRS PER: BUNDLE/CARTON 12/60

DIPPING MATERIAL PVC (Vinyl)





INNER MATERIAL SPECIFICATION Nylon

OUTER MATERIAL SPECIFICATION Polyvinyl chloride

COMPLIANCE





TP TC 019:2011



EN ISO 21420:2020

FEATURES



TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	K	L	M	P	T
Permeation level	6	2	3	6	6
Degradation %	0,4	52,9	61,3	-9,6	26,8

SIZE		ARTICLE NUMBER	EAN
8	M	12930-8	7392626068391
9	L	12930-9	7392626068407
10	XL	12930-10	7392626068377
11	XXL	12930-11	7392626068384

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com