

jalas® GRAN PREMIO 1868W KING

EN ISO 20349-2:2017 S3, SRC, CI, HRO, HI, WG EN ISO 20345:2011 S3, SRC, CI, HRO, HI, WG ASTM F2413-18 M/I/C SD 35 PR



[Learn more](#)

HIGH BOOT FOR HOT WORK

Comfortable high boot with highest level of protection, for hot work with features such as wide last and heat-resistant upper and outsole. Perfect for welders. Specially treated leather with heat resistance para-aramid thread in the seams provides a max operating heat limit of 400°C/752°F for 30 minutes. Nail protection insert in steel, toecap in aluminium and double impact protection zones in PORON® XRD® help prevent injuries.

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- ProNose™ reinforcement
- Thinsulate™ heat insulation
- Wide fit
- KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit)
- Heat-resistant upper
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Padded boot shaft
- Ventilating insole
- Pull loops
- Water repellent
- Double shock absorption zones



PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration, harsh environments

PRIMARY AREAS OF USE

Hot work, mining, sheet-metal work, welding

PRIMARY INDUSTRIES OF USE

Metal fabrication

SPECIFICATION

TYPE Safety footwear, Boots

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Steel

FITTING Wide

COLLECTION Gran Premio

UPPER MATERIAL PU-coated leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, Thinsulate™

INSOLE FX2 Pro-X

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in Poron® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole


COLOUR Black

NET WEIGHT, (SIZE 42) 1.49 kg

COMPLIANCE



TP TC 019:2011



EN ISO 20349-2:2017
S3, SRC, CI, HRO, HI, WG

EN ISO 20345:2011
S3, SRC, CI, HRO, HI, WG

ASTM F2413-18
M/I/C
SD 35 PR

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Heat-resistant upper
- Aluminium toecap
- Oil-resistant outsole
- ProNose toe reinforcement
- Nail protection in steel
- Wide fit
- Heat-resistant outsole
- Water repellent

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3½	4	1868W-35	6408487522925
36	3	4	5	1868W-36	6408487522963
37	4	5	6	1868W-37	6408487523007
38	5	5½	6½	1868W-38	6408487523045
39	6	6½	7½	1868W-39	6408487523083
40	6½	7½	8½	1868W-40	6408487523120
41	7	8	9	1868W-41	6408487523168
42	8	9	10	1868W-42	6408487523205
43	9	9½	11	1868W-43	6408487523243
44	10	10½	11½	1868W-44	6408487523281
45	10½	11	12½	1868W-45	6408487523328
46	11	12	13	1868W-46	6408487523366
47	12	13	14	1868W-47	6408487523403
48	13	13½	14½	1868W-48	6408487523441
49	14	14½	15½	1868W-49	6408487523489
50	15	15½	16½	1868W-50	6408487523526

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com