



jalas® GRAN PREMIO 1948S METATARSAL

EN ISO 20345:2011 S3, SRC, HRO, M, CI, HI ASTM F2413-18 M/I/C Mt PR ASTM F3445-21 SR



[Learn more](#)

METATARSAL IMPACT PROTECTION BOOT

A durable boot for heavy industrial work, with extreme heat resistance and great comfort. Provides the highest protection for welding and heat. Integrated impact protection of the metatarsal part of the foot. Nitrile outsole for excellent grip and excellent shock absorption with PORON® XRD in the insole. Nail protection in plasma-treated composite and toecap in aluminium for low weight. Full grain leather for good fit. A boot with the highest level of protection and comfort.

CHARACTERISTICS

- Excellent grip
- Extra comfortable
- Excellent shock absorption
- Good fit
- High level of protection

FUNCTIONS

- ProNose toe reinforcement
- Wide fit
- KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit)
- Heat-resistant upper
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Padded boot shaft
- Pull loops
- Specially designed details
- Double shock absorption zones
- Adjustable ankle strap
- Water repellent
- Flame retardant



PREVENTS RISK OF

Toe injuries, nail penetration, metatarsal injuries

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Hot work, metalwork, sheet-metal work, welding

PRIMARY INDUSTRIES OF USE

Metal fabrication

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Wide

COLLECTION Gran Premio

UPPER MATERIAL Full-grain leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide

INSOLE FX2 Climate

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in Poron® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING Hook-and-loop


COLOUR Black, Yellow

NET WEIGHT, (SIZE 42) 1.32 kg

COMPLIANCE



TP TC 019:2011



EN ISO 20345:2011
S3, SRC, HRO, M, CI, HI

ASTM F2413-18
M/1/C
Mt PR

ASTM F3445-21
SR



ÖNORM Z 1259



DGUV 112-191

FEATURES



Anti-static properties



Ergothan Shock Absorption System



Heat-resistant upper



Aluminium toecap



Oil-resistant outsole



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Wide fit



Heat-resistant outsole



Water repellent

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	1948S-36	6408487545320
37	4	5	6	1948S-37	6408487545375
38	5	5½	6½	1948S-38	6408487545429
39	6	6½	7½	1948S-39	6408487545474
40	6½	7½	8½	1948S-40	6408487545528
41	7	8	9	1948S-41	6408487545573
42	8	9	10	1948S-42	6408487545627
43	9	9½	11	1948S-43	6408487545672
44	10	10½	11½	1948S-44	6408487545726
45	10½	11	12½	1948S-45	6408487545771
46	11	12	13	1948S-46	6408487545825
47	12	13	14	1948S-47	6408487545870
48	13	13½	14½	1948S-48	6408487545924

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com