



TEGERA® 215



[Learn more](#)

Cut resistant glove, fully lined, 0,6-0,7 mm/23-27 mil full grain goatskin of top quality, polyester, cut resistance level C, KEVLAR® fiber, Cat. II, reinforced index finger, reinforced fingertips, for precision work

CHARACTERISTICS

- High level of protection
- Durable
- Perfect fit
- Extremely good fingertip sensitivity

FUNCTIONS

- Reinforced index finger
- Reinforced fingertips



PREVENTS RISK OF

Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, harsh environments

PRIMARY AREAS OF USE

Assembly, building and construction, carpentry, installation work, hvac installation, sheet-metal work, tiling, construction, engineering, transport work, metalwork, glass industry work, wood industry work, repair work

PRIMARY INDUSTRIES OF USE

Transportation, utilities, building and construction, automotive, glass, bricks, concrete

TYPE OF WORK

Light weight

SPECIFICATION

TYPE All-round work gloves, Assembly gloves, Cut resistant gloves

CATEGORY Cat. II

PALM MATERIAL Full grain goatskin of top quality

BACK MATERIAL Polyester

LINING Fully lined

LINING MATERIAL KEVLAR® fiber

LENGTH 210-260 mm

DEXTERITY 5

COLOUR Grey, White

PAIRS PER: BUNDLE/CARTON 12/120

DISPLAY TYPE Thread

FASTENING Elasticated 180°

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) TDM: 12.2N


INNER MATERIAL SPECIFICATION Para-aramid

OUTER MATERIAL SPECIFICATION Leather, Nylon, Natural latex

COMPLIANCE



TP TC 019:2011



EN 388:2016+A1:2018 2X21C

EN ISO 21420:2020



FEATURES



SIZE		ARTICLE NUMBER	EAN
7	S	215-7	7392626014077
8	M	215-8	7392626014084
9	L	215-9	7392626014107
10	XL	215-10	7392626014114
11	XXL	215-11	7392626014121
12	3XL	215-12	7392626035508

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com