



TEGERA® INFINITY 8815



[Learn more](#)

OUR THINNEST NITRILE DIPPED CUT F

Dexterous cut resistant glove with highest cut level F, suitable for precision work. Ultra light thanks to 18 gg knitted with CRF® Omni cut resistant technology. Palm dipped with super soft nitrile foam that provides excellent grip on dry surfaces. Reinforced thumb crotch for improved longevity. Breathable materials for all day comfort. Wide range of sizes means a perfectly fitting glove for everyone. Skin friendly with Derma-test and Oeko-Tex certificate.

CHARACTERISTICS	FUNCTIONS
<ul style="list-style-type: none"> • Highest level of protection • Good fingertip sensitivity • Good grip • Extra flexible • Durable • Extra comfortable 	<ul style="list-style-type: none"> • Withstands contact heat up to 100°C • Approved for handling foodstuffs • Reinforcement between index finger and thumb • Ultra thin • Super soft



PREVENTS RISK OF

Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dry environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Engineering, metalwork, paper industry work, repair work, sheet-metal work

PRIMARY INDUSTRIES OF USE

Pulp and paper, rubber and plastic, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction, logistics, retail

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves

CATEGORY Cat. II

COLLECTION Infinity

LINING MATERIAL 18 gg, CRF® Omni Technology, HPPE, Nylon, Spandex

LENGTH 220-270 mm

DEXTERITY 5

GRIP DESIGN Foam grip pattern

COLOUR Black

PAIRS PER: BUNDLE/CARTON 6/120

DISPLAY TYPE Bulk pack

DIPPING Palm-dipped

DIPPING MATERIAL Nitrile foam, Waterbased PU

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

CUT RESISTANCE (EN ISO 13997) Cut resistance level F

CUT RESISTANCE (EN ISO 13997) TDM: 31.2N


INNER MATERIAL SPECIFICATION HPPE (High performance polyethylene), Nylon, Tungsten fibre thread, Elastane

OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE



TP TC 019:2011



Contact heat rating valid for palm area only

FEATURES



SIZE		ARTICLE NUMBER	EAN
6	XS	8815-6	7340118370965
7	S	8815-7	7340118371054
8	M	8815-8	7340118371146
9	L	8815-9	7340118371238
10	XL	8815-10	7340118371320
11	XXL	8815-11	7340118371412

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com