



With Dyneema technology. No dipping makes the glove suitable for dry environments.

TEGERA® 992



[Learn more](#)

CUT PROTECTION (C) FOR HANDLING FOOD

Comfortable, light, breathable, and durable cut protection glove with Dyneema technology, suitable for inspection and fine assembly work. No dipping makes it suitable for dry environments. Approved for handling foodstuffs. Good fingertip sensitivity.

CHARACTERISTICS

- Breathable
- Good fingertip sensitivity

FUNCTIONS

- Approved for handling foodstuffs



PREVENTS RISK OF

Cut injuries, abrasion injuries, grazes, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dry environments, clean environments

PRIMARY AREAS OF USE

Fine assembly, assembly, inspection work, machine operating, installation work, glass industry work, wood industry work

PRIMARY INDUSTRIES OF USE

Agriculture, mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction

TYPE OF WORK

Light weight

SPECIFICATION

TYPE Cut resistant gloves

CATEGORY Cat. II

LINING MATERIAL 13 gg, Dyneema®, Glass fibre thread, Polyester

LENGTH 220-260 mm

DEXTERITY 5

COLOUR White

PIECES PER: BUNDLE/CARTON 10/120

DISPLAY TYPE Bag with euro slot

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

CUT RESISTANCE (EN ISO 13997) Cut resistance level C



CUT RESISTANCE (EN ISO 13997) TDM: 15N

OUTER MATERIAL SPECIFICATION UHMWPE (Ultra high molecular weight polyethylene), Polyester, Glass fibre thread

COMPLIANCE



TP TC 019:2011



EN ISO 21420:2020



FEATURES



| SIZE | | ARTICLE NUMBER | EAN |
|------|----|----------------|---------------|
| 6 | XS | 992-6 | 7392626037014 |
| 7 | S | 992-7 | 7392626005228 |
| 8 | M | 992-8 | 7392626005235 |
| 9 | L | 992-9 | 7392626005242 |
| 10 | XL | 992-10 | 7392626005259 |

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com