



TEGERA® 106

Leather glove, half-lined, 1,0-1,1 mm full grain cowhide, cotton, jersey, Cat. II, blue, beige, reinforced index finger, reinforced fingers and thumb, elasticated 180°, for heavy work

PROPERTIES

Durable

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11

PALM MATERIAL Full grain cowhide

PALM THICKNESS 1,0-1,1 mm

BACK MATERIAL Cotton, Full grain cowhide

LINING Half-lined

LINING MATERIAL Jersey

DEXTERITY 3

CUFF STYLE Safety cuff

CUFF MATERIAL Textile

FASTENING Elasticated 180°

LENGTH RANGE 220-290 mm

COLOUR Blue, beige

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Thread

OUTER MATERIAL SPECIFICATION Leather, cotton, natural latex

INNER MATERIAL SPECIFICATION Cotton, polyester

SIZE	ART. NO.	EAN NO.
7	106-7	7392626017245
8	106-8	7392626010680
9	106-9	7392626017252
10	106-10	7392626010604
11	106-11	7392626002302

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



TEGERA® 106

FEATURES

Reinforced index finger, reinforced fingers and thumb

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Dirty environments, harsh environments

PRIMARY AREAS OF USE

Building and construction, construction, soil preparation, metalwork, mining, wood industry work


PRIMARY INDUSTRIES OF USE

Mining, metal fabrication, transportation, building and construction

TYPE OF WORK

Heavy weight

 Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10


info@ejendals.com

order@ejendals.com

www.ejendals.com



CE Cat. II



TEGERA® 106

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.