



TEGERA® 10991

Cut resistant glove, Dyneema®, Lycra®, 13 gg, cut resistance level 3, Cat. II, white, extra long, breathable, for precision work

PROPERTIES

Extremely good fingertip sensitivity, extra flexible, durable, perfect fit, extra comfortable, very breathable, light

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (COUP) Cut resistance level 3

SIZE RANGE (EU) 7, 8, 9, 10, 11

LINER MATERIAL Dyneema®, Lycra®, 13 gg

DEXTERITY 5

CUFF STYLE Extended knitwrist cuff

LENGTH RANGE 240-280 mm

COLOUR White

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Bag with euro slot

MATERIAL SPECIFICATION Elastane 30%, UHMWPE 70%

SIZE	ART. NO.	EAN NO.
7	10991-7	7392626039032
8	10991-8	7392626039049
9	10991-9	7392626039056
10	10991-10	7392626039063
11	10991-11	7392626039070

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



TEGERA® 10991

PREVENTS RISK OF

Cut injuries, abrasion injuries, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Cut risk environments

PRIMARY AREAS OF USE

Fine assembly, installation work, sheet-metal work, engineering, metalwork, glass industry work


PRIMARY INDUSTRIES OF USE

Glass, bricks, concrete, metal fabrication, automotive

TYPE OF WORK

Light weight

CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 10991

EC TYPE EXAMINATION

Notified Body: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07 France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks


Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	4	(4)
B) Resistance to cutting (Index)	3	(5)
C) Tear resistance (Newton)	4	(4)
D) Puncturing resistance (Newton)	X	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com