



TEGERA® 113

Leather glove, unlined, 0,6-0,7 mm full grain pigskin, cotton, Cat. II, blue, black, grey, white, reinforced index finger, reinforced fingertips, Velcro®, for fine assembly work

PROPERTIES

High level of protection, extremely good fingertip sensitivity, durable, good grip, perfect fit

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11

PALM MATERIAL Full grain pigskin

PALM THICKNESS 0,6-0,7 mm

BACK MATERIAL Cotton

LINING Unlined

DEXTERITY 5

FASTENING Velcro®

LENGTH RANGE 235-275 mm

COLOUR Blue, black, grey, white

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Hook with hangtag

MATERIAL SPECIFICATION Leather 50%, cotton 49%, natural latex 1%



TEGERA® 113

FEATURES

Reinforced index finger, reinforced fingertips

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Dry environments, dirty environments

PRIMARY AREAS OF USE

Assembly, machine operating, building and construction, carpentry, installation work, construction, soil preparation, engineering, transport work, machine driving, warehouse work, airport work, wood industry work, repair work, paper industry work, sanitation


PRIMARY INDUSTRIES OF USE

Automotive, transportation, utilities, building and construction, logistics, retail

TYPE OF WORK

Light weight

CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-09-03

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 113

EC TYPE EXAMINATION

Notified Body: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07 France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks


Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	1	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-09-03

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com