



## TEGERA® 115

Leather glove, unlined, 0,6-0,7 mm full grain goatskin of top quality, nylon, Cat. II, grey, white, elasticated 180°, for fine assembly work

### PROPERTIES

High level of protection, extremely good fingertip sensitivity, perfect fit

### SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

PALM MATERIAL Full grain goatskin of top quality

PALM THICKNESS 0,6-0,7 mm

BACK MATERIAL Nylon

LINING Unlined

DEXTERITY 5

FASTENING Elasticated 180°

LENGTH RANGE 230-260 mm

COLOUR Grey, white

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Thread

MATERIAL SPECIFICATION Leather 50%, nylon 49%, natural latex 1%



## TEGERA® 115

### FEATURES

Reinforced index finger, reinforced fingertips

### PRIMARY PROTECTION

Prevents risk of, blisters, grazes, scratches, lacerations, contact with dirt

### PRIMARY ENVIRONMENTS OF USE

Dry environments, dirty environments

### PRIMARY AREAS OF USE

Fine assembly, assembly, inspection work, machine operating, building and construction, carpentry, installation work, construction, transport work, machine driving, warehouse work, airport work, wood industry work, gardening, repair work, service work


### PRIMARY INDUSTRIES OF USE

Automotive, transportation, utilities, building and construction, logistics, service, retail

### TYPE OF WORK

Light weight

**CE** Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-03-06

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## TEGERA® 115

### EC TYPE EXAMINATION

Notified Body: 0493 Centexbel, Technologiepark 7, BE-9052 Zwijnaarde (Gent) Belgium

### COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	0	(5)
C) Tear resistance (Newton)	0	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-03-06

3(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com