



TEGERA® 118A

Welding and heat-resistant glove, unlined, 0,7-0,8 mm full grain goatskin, split cowhide, Cat. II, yellow, white, reinforced seams, withstands welding sparks and grinding splash, elasticated 180°, for allround work

PROPERTIES

High level of protection, good fingertip sensitivity, good fit

SPECIFICATION

TYPE OF GLOVE Welding gloves

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain goatskin

PALM THICKNESS 0,7-0,8 mm

BACK MATERIAL Split cowhide

LINING Unlined

DEXTERITY 5

CUFF STYLE Safety cuff

CUFF MATERIAL Leather

FASTENING Elasticated 180°

LENGTH RANGE 310-360 mm

COLOUR Yellow, white

PAIRS PER PACKAGE/CARTON 12/60

DISPLAY Thread

MATERIAL SPECIFICATION Leather, natural latex

SIZE	ART. NO.	EAN NO.
7	118A-7	7340118312781
8	118A-8	7340118312804
9	118A-9	7340118312828
10	118A-10	7340118312729
11	118A-11	7340118312743
12	118A-12	7340118312767

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 118A

FEATURES

Withstands contact heat up to 100°C, reinforced index finger, reinforced seams, withstands welding sparks and grinding splash

PREVENTS RISK OF

Burn injuries, heat injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

All-year use, warm environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Engineering, metalwork, welding, hot work, mining




PRIMARY INDUSTRIES OF USE



Mining, oil, gas, petrochemical, metal fabrication, automotive

TYPE OF WORK

Medium weight

 Cat. II

 EN 388:2003 3121  EN 407:2004 412X4X  EN 12477:2001 + A1:2005

Type B  EN 1149-2:1997 R:12.21x10°Ω 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

2(3)


PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 118A

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

Council directive 89/686/EEC (PPE Directive)

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

EN 12477:2001 + A1:2005 Protective gloves for welders

Type B - Higher dexterity (with lower other performance)

EN 1149-2:1997 Electrostatic properties (vertical resistance)



CE Cat. II

EN 388:2003 3121 EN 407:2004 412X4X EN 12477:2001 + A1:2005

Type B EN 1149-2:1997 R:12.21x10⁶Ω

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com