



## TEGERA® 11CVA

Welding and heat-resistant glove, 0,7-0,8 mm full grain goatskin of top quality, Cat. II, yellow, white, reinforced seams, chrome free, elasticated 180°, for allround work

### PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good fit

### SPECIFICATION

TYPE OF GLOVE Welding gloves

CATEGORY Cat. II

SIZE RANGE (EU) 8, 10, 11

PALM MATERIAL Full grain goatskin of top quality

PALM THICKNESS 0,7-0,8 mm

BACK MATERIAL Full grain goatskin of top quality

DEXTERITY 5

CUFF STYLE Safety cuff

CUFF MATERIAL Leather

FASTENING Elasticated 180°

LENGTH RANGE 320-350 mm

COLOUR Yellow, white

PAIRS PER PACKAGE/CARTON 12/60

DISPLAY Thread

MATERIAL SPECIFICATION Leather, natural latex

SIZE	ART. NO.	EAN NO.
8	11CVA-8	7340118312675
10	11CVA-10	7340118312637
11	11CVA-11	7340118312651

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



## TEGERA® 11CVA

### FEATURES

Withstands contact heat up to 100°C, chrome-free tanning, reinforced seams, water repellent leather

### PREVENTS RISK OF

Burn injuries, heat injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

### PRIMARY ENVIRONMENTS OF USE

Warm surfaces, dirty environments, harsh environments

### PRIMARY AREAS OF USE

Engineering, metalwork, welding, hot work, mining

### PRIMARY INDUSTRIES OF USE




Mining, oil, gas, petrochemical, metal fabrication, automotive



### TYPE OF WORK

Light weight

2(3)

 Cat. II

 EN 388:2003 3121  EN 407:2004 412X4X  EN 12477:2001 + A1:2005

Type B  EN 1149-2:1997 R:0.38x10<sup>6</sup>Ω 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10




info@ejendals.com



order@ejendals.com

www.ejendals.com



CE Cat. II

 EN 388:2003 3121
  EN 407:2004 412X4X
  EN 12477:2001 + A1:2005

Type B 


All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

## TEGERA® 11CVA

### EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

### COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

EN 12477:2001 + A1:2005 Protective gloves for welders

Type B - Higher dexterity (with lower other performance)

EN 1149-2:1997 Electrostatic properties (vertical resistance)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com