



TEGERA® 12945

Chemical protection glove, PVC (Vinyl), seamless, nylon, granulated, Cat. III, blue, black, extra long, for heavy work

PROPERTIES

Highest level of protection, very durable, perfect fit, extra comfortable

SPECIFICATION

TYPE OF GLOVE Disposable and/or chemical resistant gloves

CATEGORY Cat. III

SIZE RANGE (EU) 8, 9, 10, 11

LINER MATERIAL Seamless, nylon

DIPPING MATERIAL PVC (Vinyl)

DEXTERITY 5

GRIP PATTERN Granulated

LENGTH RANGE 450 mm

COLOUR Blue, black

PAIRS PER PACKAGE/CARTON 12/60

AQL 0.65

OUTER MATERIAL SPECIFICATION Polyvinyl chloride 100%

INNER MATERIAL SPECIFICATION Nylon 100%


ANTIBACTERIAL/BIOCIDAL TREATMENT] Pyrithione zinc (CAS number 13463-41-7)

SIZE	ART. NO.	EAN NO.
8	12945-8	
9	12945-9	
10	12945-10	
11	12945-11	

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



CE 0120 Cat. III



TEGERA® 12945

FEATURES

Protection against chemicals, extra long, pre-curved fingers

PREVENTS RISK OF

Risk of infection, corrosive injuries, contact with dirt, contact with moisture, contact with damp, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Building and construction, HVAC installation, construction, soil preparation, concrete work, transport work, metalwork, mining, agricultural work, marine work, fishing industry work, fishing, petro-chemical work, chemical work, chemical technology work, paper industry work, decontamination, sanitation

PRIMARY INDUSTRIES OF USE

Agriculture, mining, oil, gas, petrochemical, pulp and paper, chemical, rubber and plastic, metal fabrication, automotive, building and construction

TYPE OF WORK

Heavy weight

2(4)

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-01-31

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10



info@ejendals.com

order@ejendals.com

www.ejendals.com



CE 0120 Cat. III



TEGERA® 12945

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

CHEMICAL RESISTANCE

According to EN 374-3. For details, please contact Ejendals

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

Council directive 89/686/EEC (PPE Directive)

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	4	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	3	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 374-2:2003 Protective gloves against chemicals and micro-organisms - Part 2: Determination of resistance to penetration

EN 374-3:2003 Protective gloves against chemicals and micro-organisms - Part 3: Determination of resistance to permeation by chemicals

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



TEGERA® 12945

Permeation levels are based on breakthrough times as follows

Permeation level	1	2	3	4	5	6
Minimum breakthrough times (min)	10	30	60	120	240	480

Definition of breakthrough time through the glove palm (Lugm/cm²/min)

A: Methanol (CAS Number 67-56-1) - Permeation level 2

K: Sodium hydroxide 40% (CAS number 1310-73-2) - Permeation level 6

L: Sulphuric acid 96% (CAS number 7664-93-9) - Permeation level 3

CE 0120 Cat. III

EN 388:2003
4131

EN 374-2:2003

EN 374-3:2003
AKL



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-01-31

4(4)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com