



## TEGERA® 130A

Welding and heat-resistant glove, unlined, 0,7-0,8 mm full grain goatskin, Cat. II, white, yellow, withstands contact heat up to 100°C, reinforced index finger, reinforced seams, for allround work

### PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good fit

### SPECIFICATION

TYPE OF GLOVE Welding gloves

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

PALM MATERIAL Full grain goatskin

PALM THICKNESS 0,7-0,8 mm

BACK MATERIAL Full grain goatskin

LINING Unlined

DEXTERITY 5

CUFF STYLE Safety cuff

CUFF MATERIAL Leather

LENGTH RANGE 300-350 mm

COLOUR White, yellow

PAIRS PER PACKAGE/CARTON 12/60

DISPLAY Thread

MATERIAL SPECIFICATION Leather, natural latex

1(3)

## TEGERA® 130A

### FEATURES

Withstands contact heat up to 100°C, reinforced index finger, KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit), flame retardant, withstands welding sparks and grinding splash

### PREVENTS RISK OF

Burn injuries, heat injuries, abrasion injuries, blisters, grazes, scratches, lacerations

### PRIMARY ENVIRONMENTS OF USE

Warm environments, dirty environments, harsh environments

### PRIMARY AREAS OF USE

Assembly, metalwork, welding, hot work




### PRIMARY INDUSTRIES OF USE



Mining, oil, gas, petrochemical, metal fabrication, machinery and equipment, MRO, automotive

### TYPE OF WORK

Light weight

 Cat. II

 EN 388:2003 3111  EN 407:2004 412X4X  EN 12477:2001 + A1:2005

Type B  EN 1149-2:1997 R:11,09x10<sup>6</sup>Ω 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-29

  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## TEGERA® 130A

### EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

### COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	1	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

Type B - Higher dexterity (with lower other performance)

EN 1149-2:1997 Electrostatic properties (vertical resistance)



CE Cat. II

EN 388:2003 3111 EN 407:2004 412X4X EN 12477:2001 + A1:2005

Type B EN 1149-2:1997 R:11,09x10<sup>6</sup>Ω

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-29

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com