



SIZE	ART. NO.	EAN NO.
7	132A-7	7340118312125
8	132A-8	7340118312149
9	132A-9	7340118312163
10	132A-10	7340118312040
11	132A-11	7340118312064
12	132A-12	7340118312088
13	132A-13	7340118312101

## TEGERA® 132A

Welding and heat-resistant glove, fully lined, 0,8-1,2 mm full grain goatskin of top quality, full grain cowhide of top quality, cut resistance level 4, cut resistance level C, KEVLAR® fiber, Cat. II, brown, black, reinforced seams, water and oil repellent, elasticated 180°, for allround work

### PROPERTIES

High level of protection, good fingertip sensitivity, durable, good grip, perfect fit

### SPECIFICATION

TYPE OF GLOVE Welding gloves

CATEGORY Cat. II

CUT RESISTANCE (COUP) Cut resistance level 4

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 15.03

SIZE RANGE (EU) 7, 8, 9, 10, 11, 12, 13

PALM MATERIAL Full grain goatskin of top quality

PALM THICKNESS 0,8-1,2 mm

BACK MATERIAL Full grain cowhide of top quality

LINING Fully lined

LINING MATERIAL KEVLAR® fiber

DEXTERITY 3

CUFF STYLE Safety cuff

CUFF MATERIAL Leather

FASTENING Elasticated 180°

LENGTH RANGE 310-370 mm

COLOUR Brown, black

PAIRS PER PACKAGE/CARTON 12/60

DISPLAY Thread

OUTER MATERIAL SPECIFICATION Leather, natural latex

MIDDLE MATERIAL SPECIFICATION Para-aramid

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 132A

### FEATURES

Cut resistant according to EN 388:2003 level 4, withstands contact heat up to 100°C, reinforced seams, water and oil repellent

### PREVENTS RISK OF

Burn injuries, heat injuries, cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with damp, contact with oil

### PRIMARY ENVIRONMENTS OF USE

Warm environments, moist environments, oily and greasy environments, dirty environments, harsh environments

### PRIMARY AREAS OF USE

Sheet-metal work, engineering, metalwork, welding, hot work, mining



### PRIMARY INDUSTRIES OF USE



Mining, oil, gas, petrochemical, metal fabrication, machinery and equipment, MRO, automotive

### TYPE OF WORK

Medium weight

 Cat. II

 EN 388:2003 3432  EN 407:2004 41324X  EN 12477:2001 + A1:2005

Type A  EN 1149-2:1997 R.0.130x10°Ω 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

2(3)

  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com



order@ejendals.com

www.ejendals.com



CE Cat. II

 EN 388:2003 3432
  EN 407:2004 41324X
  EN 12477:2001 + A1:2005

Type A  EN 1149-2:1997 R:0.130x10<sup>9</sup>Ω
 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

## TEGERA® 132A

### EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

### COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	4	(5)
C) Tear resistance (Newton)	3	(4)
D) Puncturing resistance (Newton)	2	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

EN 12477:2001 + A1:2005 Protective gloves for welders

Type A - Lower dexterity (with higher other performance)

EN 1149-2:1997 Electrostatic properties (vertical resistance)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com