



TEGERA® 135

Leather glove, unlined, 0,6-0,7 mm full grain goatskin, nylon, Cat. II, blue, white, reinforced index finger, reinforced fingertips, elasticated 180°, for fine assembly work

PROPERTIES

High level of protection, extremely good fingertip sensitivity, durable, good fit

SPECIFICATION

TYPE OF GLOVE Gloves for general use, minimal risks

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

PALM MATERIAL Full grain goatskin

PALM THICKNESS 0,6-0,7 mm

BACK MATERIAL Nylon

LINING Unlined

DEXTERITY 5

FASTENING Elasticated 180°

COLOUR Blue, white

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Thread

MATERIAL SPECIFICATION Leather 50%, nylon 49%, natural latex 1%

SIZE	ART. NO.	EAN NO.
6	135-6	7392626032545
7	135-7	7392626032552
8	135-8	7392626032569
9	135-9	7392626032576
10	135-10	7392626032583
11	135-11	7392626032590

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



TEGERA® 135

FEATURES

Reinforced index finger, reinforced fingertips

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Dry environments, dirty environments

PRIMARY AREAS OF USE

Assembly, inspection work, machine operating, building and construction, carpentry, installation work, construction, soil preparation, transport work, machine driving, warehouse work, airport work, gardening, repair work, shop work

PRIMARY INDUSTRIES OF USE

Automotive, transportation, utilities, building and construction, logistics

TYPE OF WORK

Light weight

 Cat. II

EN 420:2003



EN 388:2003
2010



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 135

COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	0	(5)
C) Tear resistance (Newton)	1	(4)
D) Puncturing resistance (Newton)	0	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II

EN 420:2003



EN 388:2003
2010



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com