



TEGERA® 139

Heat-resistant glove, fully lined, 0,9-1,1 mm split cowhide, cotton, cut resistance level B, KEVLAR® fiber, Cat. III, black, yellow, reinforced index finger, reinforced fingers and thumb, elasticated 180°, for allround work

PROPERTIES

High level of protection, good fingertip sensitivity, durable, good fit

SPECIFICATION

TYPE OF GLOVE Heat protection gloves

CATEGORY Cat. III

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 9,24

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11, 12, 13, 14, 15

PALM MATERIAL Split cowhide

PALM THICKNESS 0,9-1,1 mm

BACK MATERIAL Cotton

LINING Fully lined

LINING MATERIAL KEVLAR® fiber

DEXTERITY 1

CUFF STYLE Safety cuff

CUFF MATERIAL Textile

FASTENING Elasticated 180°

LENGTH RANGE 265-305 mm

COLOUR Black, yellow

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Thread

OUTER MATERIAL SPECIFICATION Cotton 50%, leather 49%, natural latex 1%

INNER MATERIAL SPECIFICATION Para-aramid 100%

SIZE	ART. NO.	EAN NO.
6	139-6	7392626049482
7	139-7	7392626039339
8	139-8	7392626039346
9	139-9	7392626039353
10	139-10	7392626039360
11	139-11	7392626039377
12	139-12	7392626039384
13	139-13	7392626039391
14	139-14	7392626046238
15	139-15	7392626046245

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



TEGERA® 139

FEATURES

Withstands contact heat up to 100°C, reinforced index finger, reinforced fingers and thumb, reflector

PREVENTS RISK OF

Burn injuries, heat injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Warm environments, harsh environments

PRIMARY AREAS OF USE

Sheet-metal work, tiling, metalwork, hot work, mining


PRIMARY INDUSTRIES OF USE

Mining, automotive, building and construction

TYPE OF WORK

Medium weight

CE Cat. III



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 139

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION


EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

EN 1149-2:1997 Electrostatic properties (vertical resistance)



CE Cat. III



EN 388:2003
4244

EN 407:2004
41324X

EN 1149-2:1997
R:1,34x10⁹Ω



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com