



TEGERA® 13

Leather glove, unlined, 0,7-0,8 mm full grain goatskin, cotton, Cat. II, blue, black, white, reinforced index finger, reinforced fingers and thumb, Velcro®, for assembly work

PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good grip, good fit, comfortable

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11

PALM MATERIAL Full grain goatskin

PALM THICKNESS 0,7-0,8 mm

BACK MATERIAL Cotton

LINING Unlined

DEXTERITY 5

CUFF MATERIAL Textile

FASTENING Velcro®

LENGTH RANGE 235-270 mm

COLOUR Blue, black, white

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Hook with hangtag

MATERIAL SPECIFICATION Leather 50%, cotton 45%, natural latex 5%

1(3)



TEGERA® 13

FEATURES

Reinforced index finger, reinforced fingertips, reinforced thumb

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Dry environments, dirty environments

PRIMARY AREAS OF USE

Assembly, inspection work, machine operating, building and construction, carpentry, installation work, construction, soil preparation, concrete work, engineering, transport work, machine driving, warehouse work, airport work, wood industry work, gardening, repair work, paper industry work, shop work


PRIMARY INDUSTRIES OF USE

Automotive, transportation, building and construction, logistics, service, retail

TYPE OF WORK

Light weight

CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-28

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 13

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks


Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	0	(5)
C) Tear resistance (Newton)	0	(4)
D) Puncturing resistance (Newton)	0	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-28

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com