



## TEGERA® 14

Leather glove, 0,6-0,7 mm full grain goatskin, cotton, Cat. II, blue, black, white, reinforced index finger, reinforced fingers and thumb, for assembly work

### PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good grip, good fit, comfortable

### SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11

PALM MATERIAL Full grain goatskin

PALM THICKNESS 0,6-0,7 mm

BACK MATERIAL Cotton

DEXTERITY 4

CUFF STYLE Extended safety cuff

CUFF MATERIAL Textile

LENGTH RANGE 265-295 mm

COLOUR Blue, black, white

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Thread

MATERIAL SPECIFICATION Cotton 55%, leather 44%, natural latex 1%



## TEGERA® 14

### FEATURES

Reinforced index finger, reinforced fingers and thumb

### PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

### PRIMARY ENVIRONMENTS OF USE

Dry environments, clean environments

### PRIMARY AREAS OF USE

Assembly, machine operating, building and construction, carpentry, installation work, construction, soil preparation, concrete work, engineering, transport work, machine driving, warehouse work, airport work, gardening, repair work, shop work


### PRIMARY INDUSTRIES OF USE

Automotive, transportation, utilities, building and construction, logistics, service, retail

### TYPE OF WORK

Light weight

 Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-28

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

#### EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## TEGERA® 14

### EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

### COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks


Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	0	(5)
C) Tear resistance (Newton)	0	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-28

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com