



AQUATHAN®



Thinsulate
INSULATION

TEGERA® 191

Leather glove, winter-lined, 1,1 - 1,4 mm full grain cowhide of top quality, Thinsulate™ 200g, Cat. II, black, white, reinforced thumb, waterproof, string lock, for allround work

PROPERTIES

Good fingertip sensitivity, flexible, durable, good grip, perfect fit, extremely warm

SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 9, 10, 11, 12

PALM MATERIAL Full grain cowhide of top quality

PALM THICKNESS 1,1 - 1,4 mm

BACK MATERIAL Full grain cowhide of top quality

LINING Winter-lined

LINING MATERIAL Thinsulate™ 200g

CLO LINING 3,3 m²-K/W

DEXTERITY 2

CUFF STYLE Extended safety cuff

CUFF MATERIAL Textile

FASTENING String lock

LENGTH RANGE 342-396 mm

COLOUR Black, white

PAIRS PER PACKAGE/CARTON 3/30

DISPLAY Hook with hangtag

OUTER MATERIAL SPECIFICATION Leather 50%, polyester 49%, natural latex 1%

MIDDLE MATERIAL SPECIFICATION Polyethylene 100%

INNER MATERIAL SPECIFICATION Polyester 100%

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 191

FEATURES

Extra long, reinforced thumb, waterproof

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with moisture, contact with damp, contact with cold

PRIMARY ENVIRONMENTS OF USE

Outdoors, cold environments, wet environments, moist environments, harsh environments

PRIMARY AREAS OF USE

Machine operating, construction, soil preparation, machine driving, warehouse work, airport work, mining, repair work, military work, marine work, fishing industry work, fishing, hunting

PRIMARY INDUSTRIES OF USE



Transportation, building and construction, logistics

TYPE OF WORK

Medium weight



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-30

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10


info@ejendals.com


order@ejendals.com

www.ejendals.com



CE Cat. II

 EN 388:2003
2222

 EN 511:2006
330



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-30

TEGERA® 191

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

| Property | Level Achieved | (Maximum Performance) |
|------------------------------------------------|----------------|-----------------------|
| A) Resistance to abrasion (No. of revolutions) | 2 | (4) |
| B) Resistance to cutting (Index) | 2 | (5) |
| C) Tear resistance (Newton) | 2 | (4) |
| D) Puncturing resistance (Newton) | 2 | (4) |

EN 388 - Testing (specifies the requirements that apply for each safety level).

| Level of protection/Performance level | 1 | 2 | 3 | 4 | 5 |
|------------------------------------------------|-----|-----|------|------|------|
| A) Resistance to abrasion (No. of revolutions) | 100 | 500 | 2000 | 8000 | |
| B) Resistance to cutting (Index) | 1,2 | 2,5 | 5,0 | 10,0 | 20,0 |
| C) Tear resistance (Newton) | 10 | 25 | 50 | 75 | |
| D) Puncturing resistance (Newton) | 20 | 60 | 100 | 150 | |

EN 511:2006 Protective gloves against cold

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com