



## TEGERA® 198

Leather glove, half-lined, 1,0-1,2 mm full grain cowhide, nylon, jersey, Cat. II, green high-viz, white, high-viz colour, reflector, elasticated 180°, for heavy work

### PROPERTIES

High level of protection, durable

### SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 8, 10

PALM MATERIAL Full grain cowhide

PALM THICKNESS 1,0-1,2 mm

BACK MATERIAL Nylon

LINING Half-lined

LINING MATERIAL Jersey

DEXTERITY 2

CUFF STYLE Safety cuff

CUFF MATERIAL Textile

FASTENING Elasticated 180°

LENGTH RANGE 240-260 mm

COLOUR Green high-viz, white

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Thread

OUTER MATERIAL SPECIFICATION Leather, nylon, natural latex

INNER MATERIAL SPECIFICATION Cotton

SIZE	ART. NO.	EAN NO.
8	198-8	7392626013100
10	198-10	7392626012677

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



## TEGERA® 198

### FEATURES

High-viz colour, reinforced index finger, reinforced fingers and thumb, reflector

### PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

### PRIMARY ENVIRONMENTS OF USE

Dark environments, all-year use

### PRIMARY AREAS OF USE

Building and construction, carpentry, construction, soil preparation, transport work, machine driving, airport work

### PRIMARY INDUSTRIES OF USE


Transportation, building and construction

### TYPE OF WORK

Heavy weight

2(3)

 Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10


info@ejendals.com

order@ejendals.com

www.ejendals.com



CE Cat. II



## TEGERA® 198

### EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

### COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.