



## TEGERA® 215

Cut resistant glove, fully lined, 0,6-0,7 mm full grain goatskin of top quality, cut resistance level 3, cut resistance level B, KEVLAR® fiber, Cat. II, grey, white, reinforced index finger, reinforced fingertips, elasticated 180°, for precision work

### PROPERTIES

High level of protection, extremely good fingertip sensitivity, durable, perfect fit

### SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (COUP) Cut resistance level 3

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 11,8

SIZE RANGE (EU) 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain goatskin of top quality

PALM THICKNESS 0,6-0,7 mm

LINING Fully lined

LINING MATERIAL KEVLAR® fiber

DEXTERITY 3

FASTENING Elasticated 180°

LENGTH RANGE 210-260 mm

COLOUR Grey, white

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Thread

OUTER MATERIAL SPECIFICATION Leather 55%, nylon 44%, natural latex 1%

INNER MATERIAL SPECIFICATION Para-aramid 100%

1(3)

## TEGERA® 215

### FEATURES

Cut resistant according to 388:2003 level 3, cut resistant according to 388:2016 level C, reinforced index finger, reinforced fingertips

### PREVENTS RISK OF

Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations

### PRIMARY ENVIRONMENTS OF USE

Harsh environments

### PRIMARY AREAS OF USE

Assembly, inspection work, machine operating, building and construction, carpentry, installation work, HVAC installation, sheet-metal work, tiling, construction, soil preparation, concrete work, engineering, transport work, machine driving, airport work, metalwork, glass industry work, wood industry work, gardening, repair work, sanitation

### PRIMARY INDUSTRIES OF USE


Glass, bricks, concrete, automotive, transportation, utilities, building and construction

### TYPE OF WORK

Light weight



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-04-25

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## TEGERA® 215

### EC TYPE EXAMINATION

Notified Body: 0493 Centexbel, Technologiepark 7, BE-9052 Zwijnaarde (Gent) Belgium

### COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	3	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	2	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-04-25

3(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com