



TEGERA® 230

Chemical protection glove, 0,67 mm latex, neoprene, diamond grip pattern, flock-lined, Cat. III, blue, yellow, for allround work

PROPERTIES

Flexible, durable, good fit

SPECIFICATION

TYPE OF GLOVE Disposable and/or chemical resistant gloves

CATEGORY Cat. III

SIZE RANGE (EU) 7, 8, 9, 10, 11

MATERIAL Latex, neoprene

THICKNESS 0,67 mm

INSIDE Flock-lined

DEXTERITY 5

GRIP PATTERN Diamond grip pattern

LENGTH RANGE 320 mm

COLOUR Blue, yellow

PAIRS PER PACKAGE/CARTON 12/144

AQL 0.65

MATERIAL SPECIFICATION Natural latex 75%, chloroprene 25%

1(4)



TEGERA® 230

FEATURES

Protection against chemicals, approved for handling foodstuffs

PREVENTS RISK OF

Corrosive injuries, contact with chemicals, contact with moisture, contact with damp

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Chemical work, chemical technology work, laboratory work





PRIMARY INDUSTRIES OF USE

Agriculture, chemical, rubber and plastic

TYPE OF WORK

Medium weight

CE 0321 Cat. III

 EN 388:2003 4121  EN 374-2:2003  EN 374-3:2003 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-28

2(4)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10





info@ejendals.com

order@ejendals.com

www.ejendals.com



CE 0321 Cat. III




All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-28

TEGERA® 230

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

CHEMICAL RESISTANCE

According to EN 374-3. For details, please contact Ejendals

COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

Council directive 89/686/EEC (PPE Directive)

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	4	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

Suitable for contact with foodstuffs

EN 374-2:2003 Protective gloves against chemicals and micro-organisms - Part 2: Determination of resistance to penetration

EN 374-3:2003 Protective gloves against chemicals and

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com



TEGERA® 230

micro-organisms - Part 3: Determination of resistance to permeation by chemicals

Permeation levels are based on breakthrough times as follows

Permeation level	1	2	3	4	5	6
Minimum breakthrough times (min)	10	30	60	120	240	480

Definition of breakthrough time through the glove palm (Lugm/cm²/min)

A: Methanol (CAS Number 67-56-1) - Permeation level 1

K: Sodium hydroxide 40% (CAS number 1310-73-2) - Permeation level 6

L: Sulphuric acid 96% (CAS number 7664-93-9) - Permeation level 4

CE 0321 Cat. III

EN 388:2003
4121

EN 374-2:2003

EN 374-3:2003



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-28

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com