



TEGERA® 235

Leather glove, winter-lined, 0,6-0,7 mm full grain goatskin, nylon, fleece, Cat. II, black, green, white, reinforced index finger, reinforced fingertips, elasticated 360°, for precision work

PROPERTIES

Good fingertip sensitivity, flexible, durable, good grip, good fit, comfortable

SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11

PALM MATERIAL Full grain goatskin

PALM THICKNESS 0,6-0,7 mm

BACK MATERIAL Nylon

LINING Winter-lined

LINING MATERIAL Fleece

DEXTERITY 4

FASTENING Elasticated 360°

LENGTH RANGE 225-255 mm

COLOUR Black, green, white

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Hook with hangtag

OUTER MATERIAL SPECIFICATION Leather 50%, nylon 49%, natural latex 1%

INNER MATERIAL SPECIFICATION Polyester 100%



TEGERA® 235

FEATURES

Reinforced index finger, reinforced fingertips

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

All-year use, cold environments

PRIMARY AREAS OF USE

Assembly, machine operating, building and construction, carpentry, engineering, transport work, machine driving, warehouse work, airport work, repair work


PRIMARY INDUSTRIES OF USE


Automotive, transportation, building and construction, logistics, retail

TYPE OF WORK

Light weight

CE Cat. II

 EN 388:2003
3111

 EN 511:2006
11X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-28

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 235

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	1	(4)
D) Puncturing resistance (Newton)	1	(4)


EN 388 - Testing (specifies the requirements that apply for each safety level).


Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 511:2006 Protective gloves against cold



CE Cat. II

 EN 388:2003
3111

 EN 511:2006
11X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-28

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com