



| SIZE | ART. NO. | EAN NO. |
|------|----------|---------------|
| 8 | 255-8 | 7340118301952 |
| 9 | 255-9 | 7340118301976 |
| 10 | 255-10 | 7340118301877 |
| 11 | 255-11 | 7340118301891 |
| 12 | 255-12 | 7340118301914 |

TEGERA® 255

Cut resistant glove, fully lined, 0,6-0,7 mm full grain goatskin of top quality, cut resistance level 3, cut resistance level C, KEVLAR® fiber, Cat. II, white, reinforced seams, fibreglass-free, elasticated 180°, for assembly work

PROPERTIES

Perfect fit

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (COUP) Cut resistance level 3

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 10,3

SIZE RANGE (EU) 8, 9, 10, 11, 12

PALM MATERIAL Full grain goatskin of top quality

PALM THICKNESS 0,6-0,7 mm

LINING Fully lined

LINING MATERIAL KEVLAR® fiber

DEXTERITY 3

FASTENING Elasticated 180°

LENGTH RANGE 225-255 mm

COLOUR White

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Thread

OUTER MATERIAL SPECIFICATION Leather, natural latex

INNER MATERIAL SPECIFICATION Para-aramid

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 255

FEATURES

Cut resistant according to 388:2003 level 3, cut resistant according to 388:2016 level C, reinforced seams, heat-resistant

PREVENTS RISK OF

Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Harsh environments

PRIMARY AREAS OF USE

Assembly, sheet-metal work, engineering, metalwork

PRIMARY INDUSTRIES OF USE


Glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, building and construction

TYPE OF WORK

Medium weight



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 255

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

| Property | Level Achieved | (Maximum Performance) |
|--|----------------|-----------------------|
| A) Resistance to abrasion (No. of revolutions) | 2 | (4) |
| B) Resistance to cutting (Index) | 3 | (5) |
| C) Tear resistance (Newton) | 2 | (4) |
| D) Puncturing resistance (Newton) | 1 | (4) |

EN 388 - Testing (specifies the requirements that apply for each safety level).

| Level of protection/Performance level | 1 | 2 | 3 | 4 | 5 |
|--|-----|-----|------|------|------|
| A) Resistance to abrasion (No. of revolutions) | 100 | 500 | 2000 | 8000 | |
| B) Resistance to cutting (Index) | 1,2 | 2,5 | 5,0 | 10,0 | 20,0 |
| C) Tear resistance (Newton) | 10 | 25 | 50 | 75 | |
| D) Puncturing resistance (Newton) | 20 | 60 | 100 | 150 | |



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com