



## TEGERA® 30

Leather glove, unlined, 0,6-0,7 mm full grain goatskin of top quality, nylon, Cat. II, blue, white, reinforced index finger, elasticated 180°, for precision work

### PROPERTIES

High level of protection, extremely good fingertip sensitivity, durable, perfect fit

### SPECIFICATION

TYPE OF GLOVE ESD gloves

CATEGORY Cat. II

SIZE RANGE (EU) 5, 6, 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain goatskin of top quality

PALM THICKNESS 0,6-0,7 mm

BACK MATERIAL Nylon

LINING Unlined

DEXTERITY 4

FASTENING Elasticated 180°

LENGTH RANGE 220-260 mm

COLOUR Blue, white

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Thread

MATERIAL SPECIFICATION Leather 50%, nylon 49%, natural latex 1%

SIZE	ART. NO.	EAN NO.
5	30-5	7392626027220
6	30-6	7392626022850
7	30-7	7392626022867
8	30-8	7392626022874
9	30-9	7392626022881
10	30-10	7392626022898
11	30-11	7392626022904
12	30-12	7392626035669

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



CE Cat. II

EN 388:2003  
2000



IEC 61340-5-1:2007  
R:  $6.0 \times 10^9 \Omega$  -  $5.4 \times 10^8 \Omega$



## TEGERA® 30

### FEATURES

Reinforced index finger, ESD, conforms with IEC 61340-5-1 (ESD)

### PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, antistatic

### PRIMARY ENVIRONMENTS OF USE

Indoors, clean environments

### PRIMARY AREAS OF USE

Fine assembly, assembly, inspection work, installation work, electrical installation, electronics work

### PRIMARY INDUSTRIES OF USE

Machinery and equipment, MRO, automotive

### TYPE OF WORK

Light weight

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

#### EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-19



CE Cat. II

EN 388:2003  
2000



IEC 61340-5-1:2007  
R:  $6.0 \times 10^5 \Omega$  -  $5.4 \times 10^8 \Omega$



## TEGERA® 30

### EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

### COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	0	(5)
C) Tear resistance (Newton)	0	(4)
D) Puncturing resistance (Newton)	0	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

IEC 61340-5-1:2007 Electrostatic Discharge (ESD) resistance below 1 gigaohm

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.