

TEGERA® 310A

Textile glove, double knitted, cotton, nylon, 13 gg, Cat. II, white, for assembly work

PROPERTIES

High level of protection, good fingertip sensitivity, flexible, very durable, perfect fit, extra comfortable, breathable

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

LINER MATERIAL Double knitted, cotton, nylon, 13 gg

DEXTERITY 4

CUFF STYLE Rolled edges

CUFF MATERIAL Textile

LENGTH RANGE 215-260mm

COLOUR White

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Bulk pack

MATERIAL SPECIFICATION Nylon 60%, cotton 30%, polyester 5%, elastane 5%



SIZE	ART. NO.	EAN NO.
6	310A-6	7340118315546
7	310A-7	7340118315560
8	310A-8	7340118315584
9	310A-9	7340118315607
10	310A-10	7340118315508
11	310A-11	7340118315522

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-06

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 310A

EC TYPE EXAMINATION

Notified Body: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07 France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	2	(5)
C) Tear resistance (Newton)	4	(4)
D) Puncturing resistance (Newton)	X	(4)



EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-02-06

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com