



TEGERA® 311

Textile glove, double-stitched fingers and thumb, nylon, 13 gg, Cat. II, white, reinforced fingers and thumb, soft, for assembly work

PROPERTIES

Extremely good fingertip sensitivity, flexible, durable, comfortable

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10

LINER MATERIAL Double-stitched fingers and thumb, nylon, 13 gg

DEXTERITY 5

CUFF STYLE Rolled edges

CUFF MATERIAL Textile

LENGTH RANGE 195-240 mm

COLOUR White

PAIRS PER PACKAGE/CARTON 12/120


DISPLAY Bag

MATERIAL SPECIFICATION Nylon 90%, polyester 5%, elastane 5%

1(3)



CE Cat. II



TEGERA® 311

FEATURES

Reinforced fingers and thumb, thin

PREVENTS RISK OF

Abrasion injuries, blisters, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Dry environments, clean environments

PRIMARY AREAS OF USE

Fine assembly, assembly, inspection work, installation work, warehouse work

PRIMARY INDUSTRIES OF USE

Pulp and paper, machinery and equipment, MRO, automotive

TYPE OF WORK

Light weight

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-09-20

TEGERA® 311

EC TYPE EXAMINATION

Notified Body: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07 France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks


Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	4	(4)
D) Puncturing resistance (Newton)	X	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-09-20

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com