



## TEGERA® 312

Textile glove, nylon, 13 gg, Cat. II, white, for assembly work

### PROPERTIES

Extremely good fingertip sensitivity, extra flexible, very durable, perfect fit, extra comfortable, breathable, extremely light

### SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10

LINER MATERIAL Nylon, 13 gg

DEXTERITY 5

CUFF STYLE Rolled edges

CUFF MATERIAL Textile

LENGTH RANGE 200-220-260

COLOUR White

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Bag

MATERIAL SPECIFICATION Nylon 90%, elastane 5%, polyester 5%

OUTER MATERIAL SPECIFICATION Nylon 90%, elastane 5%, polyester 5%

## TEGERA® 312

### FEATURES

Soft, elastic

### PREVENTS RISK OF

Blisters, contact with dirt

### PRIMARY ENVIRONMENTS OF USE

Dry environments, clean environments

### PRIMARY AREAS OF USE

Fine assembly, assembly, inspection work, machine operating, installation work, HVAC installation, construction, soil preparation, engineering, transport work, machine driving, warehouse work, electronics work, gardening, repair work, rescue work, security- and police work, paper industry work, cleaning, hotel- and restaurant work, care work, service work, shop work


### PRIMARY INDUSTRIES OF USE

Pulp and paper, machinery and equipment, MRO, automotive, transportation

### TYPE OF WORK

Light weight

 Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-09-20

2(3)

  
PROTECTING HANDS AND FEET

### EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

[info@ejendals.com](mailto:info@ejendals.com)

[order@ejendals.com](mailto:order@ejendals.com)

[www.ejendals.com](http://www.ejendals.com)

## TEGERA® 312

### EC TYPE EXAMINATION

Notified Body: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07 France

### COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks


Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	X	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-09-20

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com