



TEGERA® 318

Textile glove, PVC (Vinyl)-dots phthalate-free, double knitted, cotton, nylon, 13 gg, dots, Cat. II, blue, phthalate-free, for assembly work

PROPERTIES

High level of protection, good fingertip sensitivity, flexible, very durable, good fit, comfortable, breathable

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

PALM MATERIAL PVC (Vinyl)-dots phthalate-free

LINER MATERIAL Double knitted, cotton, nylon, 13 gg

DEXTERITY 5

GRIP PATTERN Dots

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

LENGTH RANGE 240-290 mm

COLOUR Blue

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Bulk pack

OUTER MATERIAL SPECIFICATION Nylon 50%, cotton 20%, polyvinyl chloride 20%, elastane 5%



TEGERA® 318

FEATURES

Withstands contact heat up to 100°C, approved for handling foodstuffs, phthalate-free

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Dry environments

PRIMARY AREAS OF USE

Assembly, installation work, engineering, repair work, foodstuff handling, food handling, shop work

PRIMARY INDUSTRIES OF USE


Food processing, automotive, transportation, utilities, logistics, facilities, service, retail


TYPE OF WORK


Medium weight

2(3)

CE Cat. II

 EN 388:2003
224X

 EN 407:2004
X1XXXX

 EN 511:2006
01X

 NOT FOR
FATTY FOOD



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-09-20

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 318

EC TYPE EXAMINATION

Notified Body: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07 France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	2	(5)
C) Tear resistance (Newton)	4	(4)
D) Puncturing resistance (Newton)	X	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	




EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

EN 511:2006 Protective gloves against cold

Suitable for contact with foodstuffs, except for fatty foods



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-09-20

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com