



TEGERA® 320

Synthetic leather glove, unlined, 0,6 mm synthetic leather, nylon, Cat. II, blue, black, knuckle protection, chrome free, Velcro®, for fine assembly work

PROPERTIES

Good fingertip sensitivity, flexible, good fit, extra comfortable

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11

PALM MATERIAL Synthetic leather

PALM THICKNESS 0,6 mm

BACK MATERIAL Nylon

LINING Unlined

DEXTERITY 4

FASTENING Velcro®

LENGTH RANGE 223-248 mm

COLOUR Blue, black

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Hook with hangtag

MATERIAL SPECIFICATION Polyurethane, nylon

1(3)

TEGERA® 320

FEATURES

Chrome free, reinforced fingertips, knuckle protection, short model

PREVENTS RISK OF

Chrome allergy, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping

PRIMARY ENVIRONMENTS OF USE

Dry environments, dirty environments

PRIMARY AREAS OF USE

Fine assembly, assembly, machine operating, installation work, HVAC installation, transport work, machine driving, warehouse work, airport work

PRIMARY INDUSTRIES OF USE

Automotive, transportation, logistics, facilities, service, retail

TYPE OF WORK

Light weight



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-28

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com



CE Cat. II



TEGERA® 320

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	0	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-28