



## TEGERA® 325

Synthetic leather glove, unlined, 0,6 mm synthetic leather, polyester, Cat. II, black, grey, blue, chrome free, breathable back, elasticated 360°, for fine assembly work

### PROPERTIES

Extremely good fingertip sensitivity, extra flexible, perfect fit, extra comfortable, very breathable

### SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 5, 6, 7, 8, 9, 10, 11, 12, 13

PALM MATERIAL Synthetic leather

PALM THICKNESS 0,6 mm

BACK MATERIAL Polyester

LINING Unlined

DEXTERITY 5

FASTENING Elasticated 360°

LENGTH RANGE 210-245 mm

COLOUR Black, grey, blue

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Thread

MATERIAL SPECIFICATION Polyurethane, polyester, nylon

1(3)

## TEGERA® 325

### FEATURES

Chrome free, breathable back, reinforced palm, reinforced seams

### PREVENTS RISK OF

Blisters, grazes, scratches, lacerations, contact with dirt

### PRIMARY ENVIRONMENTS OF USE

Dry environments, dirty environments

### PRIMARY AREAS OF USE

Fine assembly, assembly, inspection work, machine operating, building and construction, carpentry, installation work, tiling, construction, soil preparation, engineering, transport work, machine driving, warehouse work, airport work, wood industry work, gardening, repair work, paper industry work, service work, shop work

### PRIMARY INDUSTRIES OF USE

Agriculture, mining, oil, gas, petrochemical, food processing, pulp and paper, chemical, life science and electronics, automotive, transportation, utilities, logistics, HoReCa, facilities, service, retail

### TYPE OF WORK

Light weight



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-28

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

#### EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## TEGERA® 325

### EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

### COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks


Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	0	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-28

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com