



## TEGERA® 464

Heat-resistant glove, nitrile, cotton, Cat. III, grey, withstands contact heat up to 250°C, extra long, for heavy work

### PROPERTIES

High level of protection

### SPECIFICATION

TYPE OF GLOVE Heat protection gloves

CATEGORY Cat. III

SIZE RANGE (EU) 9, 10, 11

LINER MATERIAL Cotton

MATERIAL Nitrile

DEXTERITY 4

CUFF STYLE Extended safety cuff

CUFF MATERIAL Textile

LENGTH RANGE 350 mm

COLOUR Grey

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY No thread

MATERIAL SPECIFICATION Cotton 10%, polyester 60%, nitrile 30%

1(3)

## TEGERA® 464

### PREVENTS RISK OF

Burn injuries, heat injuries

### PRIMARY AREAS OF USE

Sheet-metal work, metalwork, hot work, glass industry work, kitchen work, hotel- and restaurant work

### PRIMARY INDUSTRIES OF USE

Rubber and plastic, glass, bricks, concrete, metal fabrication, HoReCa

### TYPE OF WORK

Heavy weight

2(3)

**CE** 0120 Cat. III



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-29

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

[info@ejendals.com](mailto:info@ejendals.com)

[order@ejendals.com](mailto:order@ejendals.com)

[www.ejendals.com](http://www.ejendals.com)

## TEGERA® 464

### EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

### COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	2	(5)
C) Tear resistance (Newton)	4	(4)
D) Puncturing resistance (Newton)	2	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)



CE 0120 Cat. III



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-29

**ejendals**  
PROTECTING HANDS AND FEET

#### EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com