



## TEGERA® 811

Synthetic glove, PU, palm-dipped, nylon, carbon, 15 gg, smooth finish, Cat. II, grey, white, for precision work

### PROPERTIES

Good fingertip sensitivity, flexible, durable, good grip, good fit, comfortable, breathable, light

### SPECIFICATION

TYPE OF GLOVE ESD gloves

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10

LINER MATERIAL Nylon, carbon, 15 gg

DIPPING Palm-dipped

DIPPING MATERIAL PU

DEXTERITY 5

GRIP PATTERN Smooth finish

CUFF STYLE Knitwrist cuff

LENGTH RANGE 220 - 250mm

COLOUR Grey, white

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Bag with euro slot

MATERIAL SPECIFICATION Nylon 60%, carbon thread 10%, polyurethane 30%



## TEGERA® 811

### FEATURES

ESD, conforms with IEC 61340-5-1 (ESD)

### PREVENTS RISK OF

Abrasion injuries, scratches, lacerations, antistatic

### PRIMARY ENVIRONMENTS OF USE

Dry environments, clean environments, dirty environments

### PRIMARY AREAS OF USE

Fine assembly, assembly, inspection work, installation work

### PRIMARY INDUSTRIES OF USE


Life science and electronics, machinery and equipment, MRO

### TYPE OF WORK

Light weight

2(3)

 Cat. II

 EN 388:2003  
4131



IEC 61340-5-1:2007  
R:  $6.0 \times 10^4 \Omega$  -  $1.6 \times 10^5 \Omega$



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-30

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## TEGERA® 811

### EC TYPE EXAMINATION

Notified Body: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07 France

### COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	4	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	3	(4)
D) Puncturing resistance (Newton)	1	(4)


EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 1149-2:1997 Electrostatic properties (vertical resistance)



**CE** Cat. II

 EN 388:2003  
4131



IEC 61340-5-1:2007  
R:  $6.0 \times 10^4 \Omega$  -  $1.6 \times 10^5 \Omega$



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-08-30

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com