



TEGERA® 850

Synthetic glove, PU, palm-dipped, nylon, 13 gg, Cat. II, white, breathable back, oil and grease resistant palm, for precision work

PROPERTIES

Good fingertip sensitivity, good grip, good fit, breathable, light

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10

LINER MATERIAL Nylon, 13 gg

DIPPING Palm-dipped

DIPPING MATERIAL PU

DEXTERITY 5

CUFF STYLE Knitwrist cuff

LENGTH RANGE 220 - 270 mm

COLOUR White

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Bag with euro slot

MATERIAL SPECIFICATION Nylon 80%, polyurethane 20%

1(3)

TEGERA® 850

FEATURES

Breathable back, oil and grease resistant palm

PREVENTS RISK OF

Abrasion injuries

PRIMARY ENVIRONMENTS OF USE

Dirty environments

PRIMARY AREAS OF USE

Assembly, inspection work, machine operating, building and construction, carpentry, painting, installation work, construction, machine driving, warehouse work, repair work, shop work

PRIMARY INDUSTRIES OF USE


Automotive, building and construction

TYPE OF WORK

Light weight



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-09-20

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 850

EC TYPE EXAMINATION

Notified Body: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07 France

COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks


Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	4	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	3	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-09-20

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com