



JALAS® 3100 MONZA GRIP

EN ISO 20345:2011, S1 HRO SRB

PROPERTIES Excellent grip, perfect fit, extra comfortable, breathable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Indoors

FEATURES Heat-resistant outsole, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL PU-coated leather, split leather

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Pro

FITTING Regular

SIZE RANGE (EU) 36-47



Aluminium toecap



Ergothan Shock Absorption System



Heat-resistant outsole



Anti-static properties



Oil-resistant outsole



ESD



JALAS® 3100 MONZA GRIP

EN ISO 20345:2011, S1 HRO SRB

PROPERTIES Excellent grip, perfect fit, extra comfortable, breathable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Indoors

FEATURES Heat-resistant outsole, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL PU-coated leather, split leather

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Pro

FITTING Regular

SIZE RANGE (EU) 36-47



Aluminium toecap



Ergothan Shock Absorption System



Heat-resistant outsole



Anti-static properties



Oil-resistant outsole



ESD