



jalas[®]

JALAS[®] 3108 MONZA GRIP

EN ISO 20345:2011, S1 P HRO SRB

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, breathable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Indoors, environments with risk for outsole penetration

FEATURES ProNose toe reinforcement, heat-resistant outsole, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, rear shock absorption zone, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL PU-coated leather, textile

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Pro

FITTING Regular

SIZE RANGE (EU) 36-47

CE



Aluminium toecap



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Ergothan Shock Absorption System



Heat-resistant outsole



Anti-static properties



Oil-resistant outsole



ESD



jalas[®]

JALAS[®] 3108 MONZA GRIP

EN ISO 20345:2011, S1 P HRO SRB

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, breathable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Indoors, environments with risk for outsole penetration

FEATURES ProNose toe reinforcement, heat-resistant outsole, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, rear shock absorption zone, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL PU-coated leather, textile

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Pro

FITTING Regular

SIZE RANGE (EU) 36-47

CE



Aluminium toecap



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Ergothan Shock Absorption System



Heat-resistant outsole



Anti-static properties



Oil-resistant outsole



ESD