



jalas[®]

JALAS[®] 3110 LIGHT GRIP

EN ISO 20345:2011, S2 HRO SRB

PROPERTIES Excellent grip, perfect fit, extra comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors

FEATURES Heat-resistant outsole, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL Split leather, textile

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Pro

FITTING Regular

SIZE RANGE (EU) 36-47

CE



Aluminium toecap



Ergothan Shock Absorption System



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole



jalas[®]

JALAS[®] 3110 LIGHT GRIP

EN ISO 20345:2011, S2 HRO SRB

PROPERTIES Excellent grip, perfect fit, extra comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors

FEATURES Heat-resistant outsole, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL Split leather, textile

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Pro

FITTING Regular

SIZE RANGE (EU) 36-47

CE



Aluminium toecap



Ergothan Shock Absorption System



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole