



jalas®

JALAS® 3438 ARIOSO

EN ISO 20345:2011, S1P SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, breathable, good shock absorption

PRIMARY ENVIRONMENTS OF USE Indoors, environments with risk for outsole penetration

FEATURES ProNose toe reinforcement, low weight, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, rear shock absorption zone, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL PU-coated leather, textile

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FXI Classic

FITTING Regular

SIZE RANGE (EU) 36-47

CE



Aluminium toecap



Ergothan Shock Absorption System



Nail protection in plasma-treated composite (PTC) textile



Anti-static properties



Oil-resistant outsole



ESD



ProNose toe reinforcement



jalas®

JALAS® 3438 ARIOSO

EN ISO 20345:2011, S1P SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, breathable, good shock absorption

PRIMARY ENVIRONMENTS OF USE Indoors, environments with risk for outsole penetration

FEATURES ProNose toe reinforcement, low weight, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, rear shock absorption zone, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL PU-coated leather, textile

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FXI Classic

FITTING Regular

SIZE RANGE (EU) 36-47

CE



Aluminium toecap



Ergothan Shock Absorption System



Nail protection in plasma-treated composite (PTC) textile



Anti-static properties



Oil-resistant outsole



ESD



ProNose toe reinforcement