



**jalas**<sup>®</sup>

## JALAS<sup>®</sup> 3448 LIGHT

EN ISO 20345:2011, S3 SRC

**PROPERTIES** Highest level of protection, excellent grip, perfect fit, extra comfortable, good shock absorption

**PRIMARY ENVIRONMENTS OF USE** Outdoors, environments with risk for outsole penetration, harsh environments

**FEATURES** ProNose toe reinforcement, low weight, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, rear shock absorption zone, conforms with IEC 61340-5-1 (ESD)

**UPPER MATERIAL** PU-coated leather

**SOLE MATERIAL** Plastic shank, PU outsole

**INSOLE** FX1 Classic

**FITTING** Regular

**SIZE RANGE (EU)** 36-47

CE



Aluminium toecap



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Ergothan Shock Absorption System



Water repellent



Anti-static properties



Oil-resistant outsole



ESD



**jalas**<sup>®</sup>

## JALAS<sup>®</sup> 3448 LIGHT

EN ISO 20345:2011, S3 SRC

**PROPERTIES** Highest level of protection, excellent grip, perfect fit, extra comfortable, good shock absorption

**PRIMARY ENVIRONMENTS OF USE** Outdoors, environments with risk for outsole penetration, harsh environments

**FEATURES** ProNose toe reinforcement, low weight, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, rear shock absorption zone, conforms with IEC 61340-5-1 (ESD)

**UPPER MATERIAL** PU-coated leather

**SOLE MATERIAL** Plastic shank, PU outsole

**INSOLE** FX1 Classic

**FITTING** Regular

**SIZE RANGE (EU)** 36-47

CE



Aluminium toecap



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Ergothan Shock Absorption System



Water repellent



Anti-static properties



Oil-resistant outsole



ESD