



jalas® *mSport*

JALAS® 3468A LIGHT SPORT

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, good shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, environments with risk for outsole penetration

FEATURES ProNose toe reinforcement, low weight, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL Split leather, textile

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Classic

FITTING Regular

SIZE RANGE (EU) 36-47

CE



Aluminium toecap



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Ergothan Shock Absorption System



Water repellent



Anti-static properties



Oil-resistant outsole



ESD



jalas® *mSport*

JALAS® 3468A LIGHT SPORT

EN ISO 20345:2011, S3 SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, good shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, environments with risk for outsole penetration

FEATURES ProNose toe reinforcement, low weight, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL Split leather, textile

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Classic

FITTING Regular

SIZE RANGE (EU) 36-47

CE



Aluminium toecap



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Ergothan Shock Absorption System



Water repellent



Anti-static properties



Oil-resistant outsole



ESD