



jalas[®]

JALAS[®] 3520 WHITE

EN ISO 20345:2011, S2 SRC

PROPERTIES Excellent grip, perfect fit, extra comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, indoors

FEATURES Oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL PU-coated leather

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Pro

FITTING Regular

SIZE RANGE (EU) 36-47

CE



Aluminium toecap



Ergothan Shock Absorption System



Water repellent



Anti-static properties



Oil-resistant outsole



ESD



jalas[®]

JALAS[®] 3520 WHITE

EN ISO 20345:2011, S2 SRC

PROPERTIES Excellent grip, perfect fit, extra comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, indoors

FEATURES Oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL PU-coated leather

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Pro

FITTING Regular

SIZE RANGE (EU) 36-47

CE



Aluminium toecap



Ergothan Shock Absorption System



Water repellent



Anti-static properties



Oil-resistant outsole



ESD