



**jalas**<sup>®</sup>



## JALAS<sup>®</sup> 4768 FIRE

EN 15090:2012, F2A SRA CI

**PROPERTIES** Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

**PRIMARY ENVIRONMENTS OF USE** Outdoors, all-year use, environments with risk for outsole penetration, wet environments, harsh environments

**FEATURES** D30<sup>®</sup> impact protection zone, KEVLAR<sup>®</sup> thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit), heat-resistant upper, heat-resistant outsole, oil-resistant outsole, anti-static properties, padded boot shaft, ventilating insole, pull loops, waterproof, reflector, specially designed details, double shock

absorption zones, heat-resistant, withstands welding sparks and grinding splash

**UPPER MATERIAL** PU-coated leather

**SOLE MATERIAL** Solid rubber outsole

**INSOLE** FX2 Pro

**FITTING** Regular

**SIZE RANGE (EU)** 39-48

CE



Aluminium toecap



Oil-resistant outsole



Nail protection in steel



Ergothan Shock Absorption System



Heat-resistant outsole



Heat-resistant upper



Waterproof



Anti-static properties



**jalas**<sup>®</sup>



## JALAS<sup>®</sup> 4768 FIRE

EN 15090:2012, F2A SRA CI

**PROPERTIES** Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

**PRIMARY ENVIRONMENTS OF USE** Outdoors, all-year use, environments with risk for outsole penetration, wet environments, harsh environments

**FEATURES** D30<sup>®</sup> impact protection zone, KEVLAR<sup>®</sup> thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit), heat-resistant upper, heat-resistant outsole, oil-resistant outsole, anti-static properties, padded boot shaft, ventilating insole, pull loops, waterproof, reflector, specially designed details, double shock

absorption zones, heat-resistant, withstands welding sparks and grinding splash

**UPPER MATERIAL** PU-coated leather

**SOLE MATERIAL** Solid rubber outsole

**INSOLE** FX2 Pro

**FITTING** Regular

**SIZE RANGE (EU)** 39-48

CE



Aluminium toecap



Oil-resistant outsole



Nail protection in steel



Ergothan Shock Absorption System



Heat-resistant outsole



Heat-resistant upper



Waterproof



Anti-static properties