



JALAS® 6418 BIO

EN ISO 20345:2011, S1 P SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, breathable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Indoors, metal-free requirements for shoes, environments with risk for outsole penetration

FEATURES ProNose toe reinforcement, oil-resistant outsole, metal free, anti-static properties, polstered shaft edge, ventilating insole, double shock absorption zones, conforms with IEC 61340-5-1 (ESD), good environmental choice, meets the EU flower environmental criteria

UPPER MATERIAL Microfiber, textile

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Pro

FITTING Narrow/Regular

SIZE RANGE (EU) 36-47



Composite toecap



Ergothan Shock Absorption System



Nail protection in plasma-treated composite (PTC) textile



Anti-static properties



Oil-resistant outsole



ESD



ProNose toe reinforcement



JALAS® 6418 BIO

EN ISO 20345:2011, S1 P SRC

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, breathable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Indoors, metal-free requirements for shoes, environments with risk for outsole penetration

FEATURES ProNose toe reinforcement, oil-resistant outsole, metal free, anti-static properties, polstered shaft edge, ventilating insole, double shock absorption zones, conforms with IEC 61340-5-1 (ESD), good environmental choice, meets the EU flower environmental criteria

UPPER MATERIAL Microfiber, textile

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Pro

FITTING Narrow/Regular

SIZE RANGE (EU) 36-47



Composite toecap



Ergothan Shock Absorption System



Nail protection in plasma-treated composite (PTC) textile



Anti-static properties



Oil-resistant outsole



ESD



ProNose toe reinforcement